



SID

		ADDITIONAL SPECIFICATIONS LETTERTYPE / LINE-STRENGTH																			
<p>TERPS INSTRUMENT DEPARTURE CHART</p> <p style="text-align: right;">BE 01A - 01B BEAUVECHAIN (EBBE)</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 25%;">BEAUVECHAIN GND 254.900 130.375</td> <td style="width: 25%;">BEAUVECHAIN TWR 284.450 122.100</td> <td style="width: 25%;">BEAUVECHAIN APP 265.200 122.500</td> <td style="width: 25%;">BELGA RADAR 368.050 129.325</td> </tr> <tr> <td>TACAN BBE CH107</td> <td>RWY</td> <td>Knots</td> <td>60 120 180 240 300 to</td> </tr> <tr> <td></td> <td>08</td> <td>V/V (fpm)</td> <td>327 654 981 1308 1635 1000 ft</td> </tr> <tr> <td></td> <td>26</td> <td>V/V (fpm)</td> <td>327 654 981 1308 1635 1800 ft</td> </tr> </table> <p>CAUTION: a) ATC MINIMUM CLIMB</p> <p style="text-align: center;">25 NM BBE TACAN</p> <p>MSA BBE 25 NM</p> <p>EMERG SAFE ALT 100 NM 4300 TA 4500</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;"> BE 01A (RWY 05) (40) </td> <td style="width: 70%;"> <ul style="list-style-type: none"> - Climb on R-052 outbound BBE TACAN. - Contact BELGA RADAR when passing 4500 ft AMSL. - Pass 8 DME / R-052 at FL60 or below. - At 13 DME turn right, max 350 kt IAS, remain within 20 NM. - Cross R-073 at FL120 or above. - Intercept R-078 inbound BBE TACAN. - Pass BBE TACAN at FL200 or below. - Proceed to R-297 outbound BBE TACAN. </td> <td style="width: 15%; text-align: center; vertical-align: middle;"> BE AIRSTAFF 18 JUL 96 </td> </tr> </table> <p>BE01A - 01B BEAUVECHAIN (EBBE)</p> <p style="text-align: center;">51°10.15' N 005°28.27' E</p>		BEAUVECHAIN GND 254.900 130.375	BEAUVECHAIN TWR 284.450 122.100	BEAUVECHAIN APP 265.200 122.500	BELGA RADAR 368.050 129.325	TACAN BBE CH107	RWY	Knots	60 120 180 240 300 to		08	V/V (fpm)	327 654 981 1308 1635 1000 ft		26	V/V (fpm)	327 654 981 1308 1635 1800 ft	BE 01A (RWY 05) (40)	<ul style="list-style-type: none"> - Climb on R-052 outbound BBE TACAN. - Contact BELGA RADAR when passing 4500 ft AMSL. - Pass 8 DME / R-052 at FL60 or below. - At 13 DME turn right, max 350 kt IAS, remain within 20 NM. - Cross R-073 at FL120 or above. - Intercept R-078 inbound BBE TACAN. - Pass BBE TACAN at FL200 or below. - Proceed to R-297 outbound BBE TACAN. 	BE AIRSTAFF 18 JUL 96	<p>A26</p> <p>A30B</p> <p>A22</p> <p>A30</p> <p>A30B</p> <p>A19</p> <p>A26B</p> <p>A26</p> <p>A26B</p> <p>A22</p> <p>A26 / 0.35 mm</p> <p>A30B</p> <p>A26B</p> <p>A26</p> <p>A19</p> <p>A39B</p> <p>A22</p> <p>A39B</p>
BEAUVECHAIN GND 254.900 130.375	BEAUVECHAIN TWR 284.450 122.100	BEAUVECHAIN APP 265.200 122.500	BELGA RADAR 368.050 129.325																		
TACAN BBE CH107	RWY	Knots	60 120 180 240 300 to																		
	08	V/V (fpm)	327 654 981 1308 1635 1000 ft																		
	26	V/V (fpm)	327 654 981 1308 1635 1800 ft																		
BE 01A (RWY 05) (40)	<ul style="list-style-type: none"> - Climb on R-052 outbound BBE TACAN. - Contact BELGA RADAR when passing 4500 ft AMSL. - Pass 8 DME / R-052 at FL60 or below. - At 13 DME turn right, max 350 kt IAS, remain within 20 NM. - Cross R-073 at FL120 or above. - Intercept R-078 inbound BBE TACAN. - Pass BBE TACAN at FL200 or below. - Proceed to R-297 outbound BBE TACAN. 	BE AIRSTAFF 18 JUL 96																			

SID

Briefing strip SID

190													
47.5			47.5				47.5			47.5			
TERPS INSTRUMENT DEPARTURE CHART			AD ELEV 230				BE 01A - 01B BEAUVECHAIN (EBBE)						
BEAUVECHAIN GND 254.900 130.375			BEAUVECHAIN TWR 284.450 122.100			BEAUVECHAIN APP 265.200 122.500			BELGA RADAR 368.050 129.325				
TACAN BBE CH107			RWY		Knots		60	120	180	240	300	to	
			08		V/V (fpm)		327	654	981	1308	1635	1000 ft	
26		V/V (fpm)		327	654	981	1308	1635	1800 ft				

Briefing strip SID (more freq)

190														
47.5			47.5				47.5			47.5				
TERPS INSTRUMENT DEPARTURE CHART			AD ELEV 230				BE 01A - 01B BEAUVECHAIN (EBBE)							
														25 - 30
BEAUVECHAIN GND 254.900 130.375			BEAUVECHAIN TWR 284.450 122.100			BEAUVECHAIN APP 265.200 122.500			BELGA RADAR 368.050 129.325					
BEAUVECHAIN RADAR 270.725 128.300			TACAN		RWY		Knots		60	120	180	240	300	to
			BBE CH107		08		V/V (fpm)		327	654	981	1308	1635	1000 ft
26		V/V (fpm)		327	654	981	1308	1635	1800 ft					

Line-strength: 0.25

All dimensions are in mm.